

## Oil Smoke Stop

### Description

Oil Smoke Stop reduces the oil consumption of gasoline and diesel engines via the piston rings and valve guides. It prevents blue smoke and oil mist and acts against the loss in viscosity in motor oils. Oil Smoke Stop increases the compression ratio and reduces engine noise. Provides extra protection in engines with high levels of wear. Extends the service life of catalytic converters.

### Properties

- reduces oil consumption
- high shear stability
- stabilizes loss of viscosity
- prevents blue, smoky exhaust fumes

### Technical data

Color / appearance	yellow, clear
Appearance / properties	viscous liquid
Density at 20 °C	0,851 g/ml
Viscosity at 40 °C	183 mm <sup>2</sup> /s
Flash point	120 °C
Odor	characteristic
Form	liquid

### Areas of application

For all gasoline and diesel engines. Compatible with all commercially available motor oils. Not suitable for use in motorbikes with wet clutches.

### Application

One 300 ml can of Oil Smoke Stop is sufficient for 4 - 6 liters of motor oil. Do not add more than 10 %. Add to the warm motor oil during every oil change and between oil changes if oil consumption is very high.

### Available pack sizes

300 ml Can sheet metal	2122
	D-E-P
300 ml Can sheet metal	2808
	DK-N-S-FIN
300 ml Can sheet metal	8360
	GB-ARAB-F
300 ml Can sheet metal	8901
	GB-GR-I
300 ml Can sheet metal	20800
	D-GB-SLO-SRB-HR
300 ml Can sheet metal	20874
	JP
300 ml Can sheet metal	21308
	ALGERIEN-GB-ARAB-F



### Available pack sizes

300 ml Can sheet metal 21351  
D-GB-CN

**Our information is based on thorough research and may be considered reliable, although not legally binding.**