

Page 1 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ആ

Top Tec 6200 0W-20

 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Motor oil
 Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated, Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1). May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

œ

3.2 Mixtures	
Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	01-2119484627-25-XXXX
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1
CAS	64742-54-7
content %	50-<75
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
1-Decene, homopolymer, hydrogenated	
Registration number (REACH)	01-2119486452-34-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	500-183-1
CAS	68037-01-4
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-	
hydroxyphenyl)propionate	
Registration number (REACH)	01-0000015551-76-XXXX
Index	607-530-00-7
EINECS, ELINCS, NLP, REACH-IT List-No.	406-040-9
CAS	125643-61-0
content %	<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 4, H413
Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1)	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	601-337-1
CAS	114959-46-5
content %	0,1-<2
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	953-650-0
CAS	
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317
	Repr. 2, H361d
Specific Concentration Limits and ATE	Repr. 2, H361d: >=17,15 %
	· · ·

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!

Inhalation



Page 3 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

ആ

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. Sensitive individuals:

Allergic reaction possible.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Extinction powder Foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of phosphorus Oxides of sulphur Oxides of nitrogen Toxic gases Hot product gives off combustible vapours.

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping. 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.



Page 4 of 15

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities. 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid formation of oil mist. Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Under all circumstances prevent penetration into the soil.

Keep protected from direct sunlight and temperatures over 50°C.

Store cool. Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name Oil mist, mineral			
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:		
working fluids, ACGIH)			
Monitoring procedures: -	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:		Other information:	

Distillates (petroleum), hydrotreated heavy paraffinic								
Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
Environmental								
compartment								
Environment - oral (animal		PNEC	9,33	mg/kg				
feed)								
Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3				
Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg				
	Exposure route / Environmental compartment Environment - oral (animal feed) Human - inhalation	Exposure route / Environmental compartmentEffect on healthEnvironment - oral (animal feed)Environment - oral (animal feed)Human - inhalationLong term, local effectsHuman - oralLong term, systemic	Exposure route / Environmental compartmentEffect on healthDescriptorEnvironmental feed)PNECHuman - inhalationLong term, local effectsDNELHuman - oralLong term, systemicDNEL	Exposure route / Environmental compartmentEffect on healthDescriptorValueEnvironmental compartmentEffect on healthPNEC9,33Environment - oral (animal feed)PNEC9,33Human - inhalationLong term, local effectsDNEL1,2Human - oralLong term, systemicDNEL0,74	Exposure route / Environmental compartmentEffect on healthDescriptorValueUnitEnvironmental feed)PNEC9,33mg/kgHuman - inhalationLong term, local effectsDNEL1,2mg/m3Human - oralLong term, systemicDNEL0,74mg/kg			



Page 5 of 15

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	0,37	mg/kg dw	
	Environment - sediment, marine		PNEC	0,037	mg/kg dw	
	Environment - soil		PNEC	10	mg/kg dw	
	Environment - freshwater		PNEC	0,018	mg/l	
	Environment - marine		PNEC	0,002	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,018	mg/l	
	Environment - oral (animal feed)		PNEC	41,33	mg/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,74	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,93	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,67	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	6,6	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.



Page 6 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,11 Permeation time (penetration time) in minutes: 30 Minimum layer thickness in mm: 0,33 Permeation time (penetration time) in minutes: 480 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time. Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation: Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

ആ

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Green
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	There is no information available on this parameter.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	220 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	n.d.a.
Kinematic viscosity:	44,0 mm2/s (40°C)



Page 7 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

œ

No information available at present.

8,4 mm2/s (100°C) Insoluble Does not apply to mixtures. There is no information available on this parameter. 0,845 g/cm3 There is no information available on this parameter. Does not apply to liquids.

SECTION 10: Stability and reactivity

10.1 Reactivity The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. 10.4 Conditions to avoid Strong heat **10.5 Incompatible materials** Avoid contact with strong oxidizing agents. **10.6 Hazardous decomposition products**

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification). Top Tec 6200 0W-20 Organism Toxicity / effect Endpoint Unit Test method Value Notes Acute toxicity, by oral route: n.d.a. Acute toxicity, by dermal route: n.d.a. Acute toxicity, by inhalation: n.d.a. Skin corrosion/irritation: n.d.a. Serious eye damage/irritation: n.d.a. No (skin Respiratory or skin sensitisation: contact), Expert judgement, Analogous conclusion Germ cell mutagenicity: n.d.a. Carcinogenicity: n.d.a. Reproductive toxicity: n.d.a. Specific target organ toxicity n.d.a. single exposure (STOT-SE): Specific target organ toxicity n.d.a. repeated exposure (STOT-RE): Aspiration hazard: n.d.a. Symptoms: n.d.a.

Distillates (petroleum), hydrotreated heavy paraffinic								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	Analogous conclusion		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion		



Page 8 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

œ.

Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	conclusion Not irritant,
Skin conosion/imation.				Rabbit	Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
conouc oyo damago, mation.				Rabbit	Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
6 ,				typhimurium	Reverse Mutation Test)	Analogous
					,	conclusion
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative,
č ,					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	Chinese hamste
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative,
0, 1					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative,
0, 1					Erythrocyte	Analogous
					Micronucleus Test)	conclusion
Carcinogenicity:				Mouse	OECD 451	Negative,
					(Carcinogenicity Studies)	Analogous
						conclusion 78
						weeks, dermal
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative,
(Developmental toxicity):					Developmental Toxicity	Analogous
					Study)	conclusion
						dermal
Reproductive toxicity:				Rat	OECD 421	Negative,
					(Reproduction/Developm	Analogous
					ental Toxicity Screening	conclusion oral
					Test)	
Aspiration hazard:						Asp. Tox. 1
Specific target organ toxicity -	LOAEL	125	mg/kg	Rat	OECD 408 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose 90-Day Oral	conclusion
oral:					Toxicity Study in	
					Rodents)	
Symptoms:						gastrointestinal
						disturbances,
One office to mark a set of the		4000		Dabbit		diarrhoea
Specific target organ toxicity -	NOAEL	1000	mg/kg	Rabbit	OECD 410 (Repeated	Analogous
repeated exposure (STOT-RE),					Dose Dermal Toxicity -	conclusion
dermal:		0.00		Det	90-Day)	Duet Mist
Specific target organ toxicity -	NOAEL	0,22	mg/l	Rat		Dust, Mist,
repeated exposure (STOT-RE),						Analogous
inhalat.:						conclusion 4
	1		1			weeks

Endpoint	Value	11		-					
	Tuluo	Unit	Organism	Test method	Notes				
					Asp. Tox. 1				
		·		-	· · ·				
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate									
	, , , , , ,	7-9-alkyl 3-(3,5-di-tert-butyl-4-							

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	



B Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 473 (In Vitro	NegativeChinese
					Mammalian	hamster
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 474 (Mammalian	NegativeChinese
					Erythrocyte	hamster
					Micronucleus Test)	
Reproductive toxicity:	NOAEL	150-600	mg/kg	Mouse	OECD 415 (One-	
			bw/d		Generation	
					Reproduction Toxicity	
					Study)	
Carcinogenicity:				Rat		Negative,
						Analogous
						conclusion
Aspiration hazard:						Negative

11.2. Information on other hazards

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).
Top Tec 6200 0W-20

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.



Reaction mass of isome Foxicity / effect 12.5. Results of PBT	Endpoint	Time	Value	Unit	Organism	Test method	Notes No PBT
Reaction mass of isome							
	rs of: C7-9-alkvl	3-(3,5-di-t	ert-butyl-4-ł	nydroxyphe	nyl)propionate		
						Closed Bottle Test)	
iograduomty.						Biodegradability -	
12.2. Persistence and degradability:		28d	2	%		OECD 301 D (Ready	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	125	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to algae:	LC50	72h	>1000	mg/l	Scenedesmus quadricauda		
potential:							
12.3. Bioaccumulative	Log Kow	-	>6,5				measured
Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
I-Decene, homopolymer	. hydrogenated						
Other information:	AOX		0	%			
potential:	-						
12.3. Bioaccumulative	Log Pow		3,9-6			1031)	High
						Co2 Evolution Test)	
- /						Biodegradability -	5
degradability:		200		70		(Ready	biodegradable
12.2. Persistence and		28d	6	%		Respirometry Test) OECD 301 B	Not readily
						Manometric	conclusion
ieg. addonity.						Biodegradability -	Analogous
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready	Not readily biodegradable,
			01	0(Test)	NI-6
i onony to algae.		1211	2-100		a subcapitata	Growth Inhibition	conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell	Test) OECD 201 (Alga,	Analogous
, ,					a subcapitata	Growth Inhibition	
12.1. Toxicity to algae:	EC50	48h	>100	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
						Immobilisation Test)	
						Acute	
		4011	>1000	iiig/i		(Daphnia sp.	conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202	conclusion Analogous
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous
12.1. Toxicity to fish:	NUEC/NUEL	200	>1000	mg/l	Oncorhynchus mykiss	USAR	
12.1. Toxicity to fich.	NOEC/NOEL	28d	>1000	ma/l	Oncorhunatura	Test) QSAR	
· · · · · · · · · · · · · · · · · · ·					mykiss	Acute Toxicity	conclusion
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	vPvB substance Analogous
and vPvB assessment							substance, No
12.5. Results of PBT							No PBT
Foxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Distillates (petroleum), h	wdrotreated hea	w naraffi	nic				
							no AOX.
	AOA		0	/0			recipe, contains
Other information:	AOX		0	%			80%/28d: No According to the
							substance)>=
							ng organic
Other information:							DOC-elimination degree(complex
	I	Т		1		1	
Top Tec 6200 0W-20	<u>E</u>						
	2						
PDF print date: 04.08.2022							
/alid from: 12.04.2022	version: 15.03.20	122 / 0005					
Revision date / version: 12 Replacing version dated / /alid from: 12.04.2022		22 / 0005					



Page 11 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

œ.

Other organisms:	NOEC/NOEL	28d	31,6	mg/kg		OECD 217 (Soil	
						Microorganisms - Carbon	
						Transformation Test)	
12.1. Toxicity to fish:	LC50	96h	>74	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,001	mg/l	Brachydanio rerio	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Water toxicology is above the water-solubility value.
12.1. Toxicity to algae:	EC50	72h	>3	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	2-4	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.3. Bioaccumulative potential:	Log Pow		9,2				Possible@20°C
12.3. Bioaccumulative potential:	BCF	35d	260			OECD 305 (Bioconcentration - Flow-Through Fish Test)	Concentration in organisms possible.Oncorh nchus mykiss
12.4. Mobility in soil:							Adsorption in ground., To be expected
12.4. Mobility in soil:	Кос		7673- 18432			OECD 106 (Adsorption/Desor ption Using a Batch Equilibrium Method)	
Toxicity to bacteria:	IC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	EC50	19d	>100	mg/kg		OECD 208 (Terrestrial Plants, Growth Test)	Brassica rapa
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	artificial soil



0
Page 12 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.04.2022 / 0006
Replacing version dated / version: 15.03.2022 / 0005
Valid from: 12.04.2022
PDF print date: 04.08.2022
Top Tec 6200 0W-20

Toxicity to annelids:	NOEC/NOEL	56d	250	mg/kg	Eisenia foetida	OECD 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei))	artificial soil
Water solubility:			0,5	µg/l			Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no.:

(GB)

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely. Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements	
14.1. UN number or ID number:	n.a.
Transport by road/by rail (ADR/RID)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
Transport by sea (IMDG-code)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a
14.5. Environmental hazards:	Not applicable
Transport by air (IATA)	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
14.6. Special precautions for user	
Unless specified otherwise, general measures for safe transport m	
14.7. Maritime transport in bulk according to	IMO instruments
Non-dangerous material according to Transport Regulations.	

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information



Page 13 of 15

ആ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

< 0,1 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Asp. Tox. — Aspiration hazard Aquatic Chronic — Hazardous to the aquatic environment - chronic Skin Sens. — Skin sensitization Repr. — Reproductive toxicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATF Acute Toxicity Estimate BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service**



ആ Page 14 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level Dissolved organic carbon DOC dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.a. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number general aen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow International Agency for Research on Cancer IARC International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. no data available n.d.a. NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride **PVC** REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel. Total organic carbon TOC



Page 15 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.04.2022 / 0006 Replacing version dated / version: 15.03.2022 / 0005 Valid from: 12.04.2022 PDF print date: 04.08.2022 Top Tec 6200 0W-20

œ

 UN RTDG
 United Nations Recommendations on the Transport of Dangerous Goods

 VOC
 Volatile organic compounds

 vPvB
 very persistent and very bioaccumulative

 wwt
 wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.